



**Basic Principles**

- Property accesses are Left In/ Left Out only.
- U-Turn facilities for all vehicles provided at 3-4 km intervals (Up to PBS 2A)
- G-Turns provided on side roads at beginning/ end of each 10-12km link.
- P-Turns provided to trisect the 10 - 12km link.
- Treatment options vary depending on side road spacing.
- If spacing between side roads is 12 -15 km lanes can be added/ removed between median openings as well.
- If spacing between side roads is between 4-8km, only one P-Turn is generally required.

DRAWING Standard Drawing - Typical Median Opening Spacing

No.	Amendment Description	Initials	Date
A3 original	This sheet may be prepared using colour and may be incomplete if copied		

DRAWN:	Nick Browne	2 June 15
REVIEWED:	Garry Hills	
APPROVED:	Richard Burk	Manager Traffic Engineering Branch



**Department of State Growth**  
 STANDARD DRAWING  
 2+1 Typical Median Opening Application  
 For Emergency Vehicles, U-Turns, Accesses and Intersections  
 Page 1/2

<b>DO NOT SCALE</b>	
<small>Use of this drawing is governed by the conditions outlined on the DIER website. It is the users responsibility to ensure it is the current revision.</small>	
STANDARD DRAWING NUMBER	REVISION NUMBER